

Description

Fastener Length: 1-3/4", Thread Size: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | HL2181020 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-603-8862 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N HL218-10-20 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Fastener Length: | 1.740 Inches Minimum And 1.760 Inches Maximum |
| Head Style: | Straight Pan |
| Head Height: | 0.068 Inches Minimum And 0.078 Inches Maximum |
| Shank Diameter: | 0.3422 Inches Minimum And 0.3432 Inches Maximum |
| Shank Style: | Stump |
| Head Major Diameter: | 0.475 Inches Minimum And 0.505 Inches Maximum |
| Chamfer Length: | 0.0468 Inches Nominal |
| Tip Diameter: | 0.160 Inches Minimum And 0.180 Inches Maximum |
| Grip Length: | 1.245 Inches Minimum And 1.255 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 6300 Pounds Per Square Inch |
| Nominal Thread Size: | 0.3125 Inches |
| Part Name Assigned By Controlling Agency: | Protruding Shear Head Alloy Steel 1/16 Inch Grip Variation 1/32 Oversize |
| Material: | Steel Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2,color:bronze,and Cetyl Alcohol Lubrication Per Hi-shear Spec 305 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL218-10-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.