

Description

Fastener Length: 1-3/4", Thread Size: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL2181020
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-603-8862
Schedule B:	7318.24.0000
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N HL218-10-20 Specifications

Thread Class:	3a
Fastener Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.068 Inches Minimum And 0.078 Inches Maximum
Shank Diameter:	0.3422 Inches Minimum And 0.3432 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.475 Inches Minimum And 0.505 Inches Maximum
Chamfer Length:	0.0468 Inches Nominal
Tip Diameter:	0.160 Inches Minimum And 0.180 Inches Maximum
Grip Length:	1.245 Inches Minimum And 1.255 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	6300 Pounds Per Square Inch
Nominal Thread Size:	0.3125 Inches
Part Name Assigned By Controlling Agency:	Protruding Shear Head Alloy Steel 1/16 Inch Grip Variation 1/32 Oversize
Material:	Steel Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2,color:bronze,and Cetyl Alcohol Lubrication Per Hi-shear Spec 305 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL218-10-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.