

**Description**

Fastener Length: 1-3/4", Thread Size: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL2181020
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-603-8862
Schedule B:	7318.24.0000
ECCN:	EAR99



NO IMAGE  
AVAILABLE

## P/N HL218-10-20 Specifications

<b>Thread Class:</b>	3a
<b>Fastener Length:</b>	1.740 Inches Minimum And 1.760 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.068 Inches Minimum And 0.078 Inches Maximum
<b>Shank Diameter:</b>	0.3422 Inches Minimum And 0.3432 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.475 Inches Minimum And 0.505 Inches Maximum
<b>Chamfer Length:</b>	0.0468 Inches Nominal
<b>Tip Diameter:</b>	0.160 Inches Minimum And 0.180 Inches Maximum
<b>Grip Length:</b>	1.245 Inches Minimum And 1.255 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	6300 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.3125 Inches
<b>Part Name Assigned By Controlling Agency:</b>	Protruding Shear Head Alloy Steel 1/16 Inch Grip Variation 1/32 Oversize
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2,color:bronze,and Cetyl Alcohol Lubrication Per Hi-shear Spec 305 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this hl pin from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL218-10-20](https://military-fasteners.com/pins/pin_rivets/HL218-10-20) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.