

Description

Fastener Length: 13/16", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL218105
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-497-7895
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL218-10-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Err-090
Head Height:	0.068 Inches Minimum And 0.078 Inches Maximum
Width Between Flats:	0.1270 Inches Minimum And 0.1295 Inches Maximum
Shank Diameter:	0.3422 Inches Minimum And 0.3432 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.475 Inches Minimum And 0.505 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.307 Inches Minimum And 0.317 Inches Maximum
Nominal Thread Size:	0.312 Inches
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp E4340 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL218-10-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.