

Description

Fastener Length: 13/16", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL218105 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5320-01-497-7895 |
| Schedule B: | 7318.24.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N HL218-10-5 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.802 Inches Minimum And 0.822 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.068 Inches Minimum And 0.078 Inches Maximum |
| Width Between Flats: | 0.1270 Inches Minimum And 0.1295 Inches Maximum |
| Shank Diameter: | 0.3422 Inches Minimum And 0.3432 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.475 Inches Minimum And 0.505 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.307 Inches Minimum And 0.317 Inches Maximum |
| Nominal Thread Size: | 0.312 Inches |
| Material: | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp E4340 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL218-10-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.