

Description

Fastener Length: 1-3/32", Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL218129
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-612-2985
Schedule B:	7318.24.0000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N HL218-12-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.107 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.078 Inches Minimum And 0.088 Inches Maximum
Width Between Flats:	0.1582 Inches Minimum And 0.1617 Inches Maximum
Shank Diameter:	0.197 Inches Minimum And 0.217 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.585 Inches Minimum And 0.600 Inches Maximum
Grip Length:	0.562 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Shear Strength:	24600 Double Pounds Per Square Inch
Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5628 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL218-12-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.