

**Description**

Fastener Length: 1-3/32", Thread Size: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL218129
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-612-2985
Schedule B:	7318.24.0000
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N HL218-12-9 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.107 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.078 Inches Minimum And 0.088 Inches Maximum
<b>Width Between Flats:</b>	0.1582 Inches Minimum And 0.1617 Inches Maximum
<b>Shank Diameter:</b>	0.197 Inches Minimum And 0.217 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.585 Inches Minimum And 0.600 Inches Maximum
<b>Grip Length:</b>	0.562 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Shear Strength:</b>	24600 Double Pounds Per Square Inch
<b>Material:</b>	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5628 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this hl pin from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL218-12-9](https://military-fasteners.com/pins/pin_rivets/HL218-12-9) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.