

Description


Diameter: 7/32", Grip Length: 3/16", protruding shear head, oversized for hl18, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL21863
Minimum Qty (MOQ):	25
NSN:	5306-00-522-1813
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N HL218-6-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.325 Inches Minimum
Fastener Length:	0.503 Inches Minimum And 0.523 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Shoulder Diameter:	0.217 Inches Minimum First Shoulder And 0.218 Inches Maximum First Shoulder
Shoulder Length:	0.178 Inches Minimum First Shoulder And 0.198 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	35.0 Rockwell C Nominal Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL218-6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.