

P/N HL218-6-5

Description

protruding shear head - oversized for hl18 - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: HL21865

Minimum Qty (MOQ): 10

NSN: 5306-00-410-1749

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N HL218-6-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.325 Inches Minimum
Fastener Length:	0.627 Inches Minimum And 0.647 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Shoulder Diameter:	0.217 Inches Minimum First Shoulder And 0.218 Inches Maximum First Shoulder
Shoulder Length:	0.302 Inches Minimum First Shoulder And 0.322 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	28.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall Or Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacb30kk Manufacturers Standard

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL218-6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.