

Description

Fastener Length: 1-45/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL218821
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-590-4282
Schedule B:	7318.24.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N HL218-8-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Bronze
Fastener Length:	1.707 Inches Nominal
Head Style:	Straight Pan
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Width Between Flats:	0.122 Inches Minimum And 0.142 Inches Maximum
Shank Diameter:	0.250 Inches Nominal
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	1.312 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.250 Inches
Material:	Steel Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL218-8-21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.