

**Description**

Fastener Length: 1-49/64", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL218822
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-603-8790
Schedule B:	7318.24.0000
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N HL218-8-22 Specifications

<b>Thread Class:</b>	3a
<b>Fastener Length:</b>	1.760 Inches Minimum And 1.780 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.059 Inches Minimum And 0.069 Inches Maximum
<b>Shank Diameter:</b>	0.2797 Inches Minimum And 0.2807 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.387 Inches Minimum And 0.412 Inches Maximum
<b>Chamfer Length:</b>	0.0312 Inches Nominal
<b>Tip Diameter:</b>	0.122 Inches Minimum And 0.142 Inches Maximum
<b>Grip Length:</b>	1.370 Inches Minimum And 1.380 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Part Name Assigned By Controlling Agency:</b>	Protruding Shear Head Alloy Steel 1/16 Inch Grip Variation-1/32 Inch Oversize
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall

## How to Order

Order this hl pin from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL218-8-22](https://military-fasteners.com/pins/pin_rivets/HL218-8-22) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.