

Description

Fastener Length: 1-49/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL218822
Minimum Qty (MOQ):	20 EA
NSN:	5320-01-603-8790
Schedule B:	7318.24.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N HL218-8-22 Specifications

Thread Class:	3a
Fastener Length:	1.760 Inches Minimum And 1.780 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Shank Diameter:	0.2797 Inches Minimum And 0.2807 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
Chamfer Length:	0.0312 Inches Nominal
Tip Diameter:	0.122 Inches Minimum And 0.142 Inches Maximum
Grip Length:	1.370 Inches Minimum And 1.380 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Part Name Assigned By Controlling Agency:	Protruding Shear Head Alloy Steel 1/16 Inch Grip Variation-1/32 Inch Oversize
Material:	Steel Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL218-8-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.