

Description

protruding shear head, oversized for hl18, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL21886
Minimum Qty (MOQ):	20
NSN:	5320-00-494-7991
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N HL218-8-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.7600 Inches Minimum And 0.7800 Inches Maximum
Head Style:	Err-090
Head Height:	0.0590 Inches Minimum And 0.0690 Inches Maximum
Width Between Flats:	0.09470 Inches Minimum And 0.09670 Inches Maximum
Shank Diameter:	0.2797 Inches Minimum And 0.2807 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3870 Inches Minimum And 0.4120 Inches Maximum
Grip Length:	0.3700 Inches Minimum And 0.3800 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.2500 Inches
Material:	Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp E4340 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL218-8-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.