

## Description

protruding shear head, oversized for hl18, alloy steel cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	HL21886
Minimum Qty (MOQ):	20
NSN:	5320-00-494-7991
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N HL218-8-6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.7600 Inches Minimum And 0.7800 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.0590 Inches Minimum And 0.0690 Inches Maximum
<b>Width Between Flats:</b>	0.09470 Inches Minimum And 0.09670 Inches Maximum
<b>Shank Diameter:</b>	0.2797 Inches Minimum And 0.2807 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.3870 Inches Minimum And 0.4120 Inches Maximum
<b>Grip Length:</b>	0.3700 Inches Minimum And 0.3800 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.2500 Inches
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp E4340 Overall
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL218-8-6](https://military-fasteners.com/pins/pin_rivets/HL218-8-6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.