

Description

Fastener Length: 1-1/8", Thread Size: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL2191010
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-498-1564
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N HL219-10-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.125 Inches Nominal
Head Style:	Flush Countersunk
Shank Diameter:	0.3125 Inches Nominal
Shank Style:	Err-090
Head Major Diameter:	0.5001 Inches Minimum And 0.5051 Inches Maximum
Grip Length:	0.500 Inches Nominal
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.3125 Inches
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Tip Radius: 0.0468 In. Nominal
Material:	Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type2,class2,cetyl Alcohol Lube/hs Spec. 305 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL219-10-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.