

**Description**

Fastener Length: 1-1/8", Thread Size: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL2191010
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-498-1564
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N HL219-10-10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	1.125 Inches Nominal
<b>Head Style:</b>	Flush Countersunk
<b>Shank Diameter:</b>	0.3125 Inches Nominal
<b>Shank Style:</b>	Err-090
<b>Head Major Diameter:</b>	0.5001 Inches Minimum And 0.5051 Inches Maximum
<b>Grip Length:</b>	0.500 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.3125 Inches
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Tip Radius: 0.0468 In. Nominal
<b>Material:</b>	Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type2,class2,cetyl Alcohol Lube/hs Spec. 305 Fed Spec 1st Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL219-10-10](https://military-fasteners.com/rivets/pin_rivets/HL219-10-10) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.