

P/N HL219-10-20

Description

Fastener Length: 1-3/4", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: HL2191020

Minimum Qty (MOQ): 5 EA

NSN: 5320-00-231-4692

Schedule B: 7318.24.0000

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N HL219-10-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.1270 Inches Minimum And 0.1295 Inches Maximum
Shank Diameter:	0.3422 Inches Minimum And 0.3432 Inches Maximum
Head Major Diameter:	0.5001 Inches Minimum And 0.5051 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	1.255 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.312 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL219-10-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.