

**Description**

Fastener Length: 13/16", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL219105
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-497-7882
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL219-10-5 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.802 Inches Minimum And 0.822 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.1270 Inches Minimum And 0.1295 Inches Maximum
<b>Shank Diameter:</b>	0.3422 Inches Minimum And 0.3432 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.5001 Inches Minimum And 0.5051 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.307 Inches Minimum And 0.317 Inches Maximum
<b>Nominal Thread Size:</b>	0.312 Inches
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp E4340 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL219-10-5](https://military-fasteners.com/rivets/pin_rivets/HL219-10-5) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.