



★ FASTENERS

Military-Fasteners.com

P/N HL219-12-10

Description

Fastener Length: 1-11/64", Thread Size: 3/8", flush countersunk head, Hi-Lok, HL219 series

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL2191210
Minimum Qty (MOQ):	5
NSN:	5320-01-612-3000
Schedule B:	7318.24.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N HL219-12-10 Specifications

Thread Direction:	Right-hand
Fastener Length:	1.179 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.1582 Inches Minimum And 0.1617 Inches Maximum
Shank Diameter:	0.197 Inches Minimum And 0.217 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.5866 Inches Minimum And 0.5916 Inches Maximum
Grip Length:	0.625 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Shear Strength:	24600 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5628 Mil Spec Single Material Response Or Mil-s-6 49 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL219-12-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.