

Description

Fastener Length: 1-3/32", Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | HL219129 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-612-3001 |
| Schedule B: | 7318.24.0000 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N HL219-12-9 Specifications

| | |
|---|--|
| Thread Direction: | Right-hand |
| Fastener Length: | 1.107 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.1582 Inches Minimum And 0.1617 Inches Maximum |
| Shank Diameter: | 0.197 Inches Minimum And 0.217 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.5866 Inches Minimum And 0.5916 Inches Maximum |
| Grip Length: | 0.562 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.375 Inches |
| Shear Strength: | 24600 Double Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Comp E4340 Or Steel Comp 4140 Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5628 Mil Spec Single Material Response Or Mil-s-6 49 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL219-12-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.