

Description

Fastener Length: 1-21/64", Thread Size: 10-

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | HL219616 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-603-8565 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N HL219-6-16 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Fastener Length: | 1.315 Inches Minimum And 1.335 Inches Maximum |
| Head Style: | Straight Pan |
| Head Height: | 0.104 Inches Minimum And 0.119 Inches Maximum |
| Shank Diameter: | 0.2172 Inches Minimum And 0.2182 Inches Maximum |
| Shank Style: | Stump |
| Head Major Diameter: | 0.3253 Inches Minimum And 0.3303 Inches Maximum |
| Chamfer Length: | 0.015 Inches Nominal |
| Tip Diameter: | 0.104 Inches Minimum And 0.119 Inches Maximum |
| Grip Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 2000 Pounds Per Square Inch |
| Nominal Thread Size: | 10.0 Millimeters |
| Part Name Assigned By Controlling Agency: | 100 Degree Flush Shear Head Alloy Steel |
| Material: | Steel Comp 4340 Or Steel Comp 4140 Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2,color:bronze,and Cetyl-alcohol Lube Per Iii Shear Spec-305 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL219-6-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.