

Description

Fastener Length: 1-21/64", Thread Size: 10-"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL219616
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-603-8565
Schedule B:	7318.24.0000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N HL219-6-16 Specifications

Thread Class:	3a
Fastener Length:	1.315 Inches Minimum And 1.335 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.104 Inches Minimum And 0.119 Inches Maximum
Shank Diameter:	0.2172 Inches Minimum And 0.2182 Inches Maximum
Shank Style:	Stump
Head Major Diameter:	0.3253 Inches Minimum And 0.3303 Inches Maximum
Chamfer Length:	0.015 Inches Nominal
Tip Diameter:	0.104 Inches Minimum And 0.119 Inches Maximum
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	2000 Pounds Per Square Inch
Nominal Thread Size:	10.0 Millimeters
Part Name Assigned By Controlling Agency:	100 Degree Flush Shear Head Alloy Steel
Material:	Steel Comp 4340 Or Steel Comp 4140 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2,color:bronze,and Cetyl-alcohol Lube Per Iii Shear Spec-305 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL219-6-16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.