

Description

Fastener Length: 1-21/64", Thread Size: 10-

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL219616
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-603-8565
Schedule B:	7318.24.0000
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N HL219-6-16 Specifications

<b>Thread Class:</b>	3a
<b>Fastener Length:</b>	1.315 Inches Minimum And 1.335 Inches Maximum
<b>Head Style:</b>	Straight Pan
<b>Head Height:</b>	0.104 Inches Minimum And 0.119 Inches Maximum
<b>Shank Diameter:</b>	0.2172 Inches Minimum And 0.2182 Inches Maximum
<b>Shank Style:</b>	Stump
<b>Head Major Diameter:</b>	0.3253 Inches Minimum And 0.3303 Inches Maximum
<b>Chamfer Length:</b>	0.015 Inches Nominal
<b>Tip Diameter:</b>	0.104 Inches Minimum And 0.119 Inches Maximum
<b>Grip Length:</b>	0.990 Inches Minimum And 1.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	2000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	10.0 Millimeters
<b>Part Name Assigned By Controlling Agency:</b>	100 Degree Flush Shear Head Alloy Steel
<b>Material:</b>	Steel Comp 4340 Or Steel Comp 4140 Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2,color:bronze,and Cetyl-alcohol Lube Per Iii Shear Spec-305 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL219-6-16](https://military-fasteners.com/rivets/pin_rivets/HL219-6-16) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.