

Description

Fastener Length: 1-25/64", Thread Size: 10-

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | HL219617         |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5320-01-603-8323 |
| Schedule B:        | 7318.24.0000     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

## P/N HL219-6-17 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Fastener Length:</b>                               | 1.3775 Inches Minimum And 1.3975 Inches Maximum  |
| <b>Head Style:</b>                                    | Straight Pan   |
| <b>Head Height:</b>                                   | 0.104 Inches Minimum And 0.119 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.2172 Inches Minimum And 0.2182 Inches Maximum  |
| <b>Shank Style:</b>                                   | Stump  |
| <b>Head Major Diameter:</b>                           | 0.3253 Inches Minimum And 0.3303 Inches Maximum  |
| <b>Chamfer Length:</b>                                | 0.015 Inches Nominal   |
| <b>Grip Length:</b>                                   | 0.0525 Inches Minimum And 0.0725 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 2000 Pounds Per Square Inch  |
| <b>Nominal Thread Size:</b>                           | 10.0 Millimeters   |
| <b>Part Name Assigned By Controlling Agency:</b>      | 100 Degree Flush Shear Head Alloy Steel  |
| <b>Material:</b>                                      | Steel Comp 4340 Or Steel Comp 4140 Or Steel Comp 8740 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec Single Material Response Or Mil-s-5626 Mil Spec Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2,color Bronze,and Cetyl Alcohol Lube Per Iii Shear Spec-305 Fed Spec Single Treatment Response Overall                        |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL219-6-17](https://military-fasteners.com/rivets/pin_rivets/HL219-6-17) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.