

P/N HL219-6-3

Description

Flush shear head, oversized for hl19, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: HL21963

Minimum Qty (MOQ): 25

NSN: 5320-00-544-3536

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc







^{*} See page 2 for technical characteristics

P/N HL219-6-3 Specifications

Right-hand Fastener Length: 0.503 Inches Minimum And 0.523 Inches Maximum Head Style: Flush Countersunk Width Between Flats: 0.0947 Inches Minimum And 0.0967 Inches Maximum Shank Diameter: 0.2172 Inches Minimum And 0.2182 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.3253 Inches Minimum And 0.3303 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Q-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall		
Fastener Length: 0.503 Inches Minimum And 0.523 Inches Maximum Flush Countersunk Width Between Flats: 0.0947 Inches Minimum And 0.0967 Inches Maximum Shank Diameter: 0.2172 Inches Minimum And 0.2182 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.3253 Inches Minimum And 0.3303 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Classification: Cadmium Overall Oq-p-416.ty 2.cl 3 Fed Spec Single Treatment Response Overall Oq-p-416.ty 2.cl 3 Fed Spec Single Treatment Response Overall	Thread Class:	3a
Head Style: Flush Countersunk Width Between Flats: 0.0947 Inches Minimum And 0.0967 Inches Maximum Shank Diameter: 0.2172 Inches Minimum And 0.2182 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.3253 Inches Minimum And 0.3303 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Surface Treatment: Cadmium Overall Oq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Thread Direction:	Right-hand
Width Between Flats: 0.0947 Inches Minimum And 0.0967 Inches Maximum Shank Diameter: 0.2172 Inches Minimum And 0.2182 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Bead Major Diameter: 0.3253 Inches Minimum And 0.3303 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Oq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Fastener Length:	0.503 Inches Minimum And 0.523 Inches Maximum
Shank Diameter: 0.2172 Inches Minimum And 0.2182 Inches Maximum Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.3253 Inches Minimum And 0.3303 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Surface Treatment Document And Q-p-416.ty 2,cl 3 Fed Spec Single Treatment Response Overall	Head Style:	Flush Countersunk
Shank Style: Pin-rivet, Straight, Threaded Head Major Diameter: 0.3253 Inches Minimum And 0.3303 Inches Maximum Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Head Major Diameter: Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Shank Diameter:	0.2172 Inches Minimum And 0.2182 Inches Maximum
Lubrication: Cetyl Alcohol Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Cadmium Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Shank Style:	Pin-rivet, Straight, Threaded
Grip Length: 0.193 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Head Major Diameter:	0.3253 Inches Minimum And 0.3303 Inches Maximum
Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Surface Treatment: Cadmium Overall Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Classification:	Lubrication:	Cetyl Alcohol
Minimum Tensile Strength: Nominal Thread Size: 0.190 Inches Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Cadmium Overall Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Grip Length:	0.193 Inches Maximum
Nominal Thread Size: 5. Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	32
Shear Strength: 95000 Single Pounds Per Square Inch Countersink Angle: 100.0 Degrees Nominal Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Cadmium Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle: Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Cadmium Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Nominal Thread Size:	0.190 Inches
Material: Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Material Document And Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Shear Strength:	95000 Single Pounds Per Square Inch
Material Document And Classification: Surface Treatment Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Countersink Angle:	100.0 Degrees Nominal
Classification: Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Material Document And Classification:	
Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall
Thread Series Designator: Unjf	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL219-6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin_rivets/HL219-6-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/pins/pin_rivets/HL219-6-3 and selecting the quantity you want then click "add to cart".