

## P/N HL219-8-14

### **Description**

Fastener Length: 1-17/64", Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: HL219814

Minimum Qty (MOQ): 20 EA

NSN: 5320-00-280-3503

Schedule B: 7318.24.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N HL219-8-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.260 Inches Minimum And 1.280 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.094 Inches Minimum And 0.096 Inches Maximum
Shank Diameter:	0.2797 Inches Minimum And 0.2807 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.421 Inches Minimum And 0.426 Inches Maximum
Lubrication:	Cetyl Alcohol
End Item Identification:	W/s:aircraft, Stratolifter C-135
Grip Length:	0.880 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/pin\_rivets/HL219-8-14">https://military-fasteners.com/rivets/pin\_rivets/HL219-8-14</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.