

Description

100°, flush shear head - oversized for hl19 - alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL21986
Minimum Qty (MOQ):	10
NSN:	5320-01-185-8720
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HL219-8-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Identification Code Color:	Bronze
Fastener Length:	0.760 Inches Minimum And 0.780 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0947 Inches Minimum And 0.0967 Inches Maximum
Shank Diameter:	0.2797 Inches Minimum And 0.2807 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.4260 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.380 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.250 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL219-8-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.