

P/N HL21PB5-2

Description

flush ms24694 tension head, alloy steel cadmium plated, HL21 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

HL21PB-5-2

SKU / Model: HL21PB52

Minimum Qty (MOQ): 20

NSN: 5320-01-081-1307

Schedule B: 7318.24.0000

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









^{*} See page 2 for technical characteristics

P/N HL21PB5-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.427 Inches Minimum And 0.447 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0801 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3304 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.130 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.164 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL21PB5-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.