

Description

Diameter: 3/16", Grip Length: 7/16", flush tension head, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HL21PB67 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5320-00-757-5506 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N HL21PB6-7 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.753 Inches Minimum And 0.773 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.079 Inches Minimum And 0.081 Inches Maximum |
| Shank Diameter: | 0.189 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Pin-riquet, Straight, Threaded |
| Head Major Diameter: | 0.377 Inches Minimum And 0.381 Inches Maximum |
| Grip Length: | 0.443 Inches Maximum |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Nominal Thread Size: | 0.190 Inches |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL21PB6-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.