

**Description**

Fastener Length: 1-17/64", Thread: 1/4-28, Head Width: 3/32", Thread Length: 25/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[HL21PB-8-14](#)

SKU / Model:	HL21PB814
Minimum Qty (MOQ):	5
NSN:	5305-00-933-7291
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N HL21PB8-14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.380 Inches Minimum And 0.410 Inches Maximum
<b>Fastener Length:</b>	1.260 Inches Minimum And 1.280 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.464 Inches Minimum And 0.510 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.870 Inches Minimum And 0.880 Inches Maximum
<b>Width Across Flats:</b>	0.095 Inches Minimum And 0.097 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Special Features:</b>	Drilled Hole Thd End 0.122 To 0.142 In. Dia,0.200 In. Deep
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rievet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL21PB8-14](https://military-fasteners.com/pins/pin_rivets/HL21PB8-14) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.