

**Description**

Thread Size: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL22512
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-401-5711
Schedule B:	7616.99.5090
ECCN:	9A991
National Motor Freight:	013120, Aluminum Article Noi Sub 6

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL22-5-12 Specifications

<b>Thread Class:</b>	3a
<b>Fastener Length:</b>	1.052 Inches Minimum And 1.072 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.045 Inches Minimum And 0.055 Inches Maximum
<b>Width Between Flats:</b>	0.0635 Inches Minimum And 0.0645 Inches Maximum
<b>Shank Diameter:</b>	0.1625 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.242 Inches Minimum And 0.262 Inches Maximum
<b>Unable To Decode:</b>	Unable To Decode
<b>Grip Length:</b>	0.745 Inches Minimum And 0.755 Inches Maximum
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-430,alloy 7075 Fed Spec Single Material Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this hl pin from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL22-5-12](https://military-fasteners.com/pins/pin_rivets/HL22-5-12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.