



[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N HL22-5-2**

## Description

Diameter: 5/32", Grip Length: 1/8", protruding shear head, aluminum alloy, anodized

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	HL2252
Minimum Qty (MOQ):	10
NSN:	5320-01-491-9421
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



\* See page 2 for technical characteristics

## P/N HL22-5-2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.427 Inches Minimum And 0.447 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.045 Inches Minimum And 0.060 Inches Maximum
<b>Width Between Flats:</b>	0.0635 Inches Minimum And 0.0645 Inches Maximum
<b>Shank Diameter:</b>	0.1625 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.242 Inches Minimum And 0.262 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.120 Inches Minimum And 0.130 Inches Maximum
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-225/9 Fed Spec 1st Material Response Overall Or Qq-a-430 Fed Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Ams-a-8625 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL22-5-2](https://military-fasteners.com/pins/pin_rivets/HL22-5-2) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.