

Description

Fastener Length: 1-11/16", Thread Size: 5/32", shear head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL22522
Minimum Qty (MOQ):	2
NSN:	5320-00-343-5362
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HL22-5-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.677 Inches Minimum And 1.697 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.060 Inches Maximum
Width Between Flats:	0.064 Inches Minimum And 0.065 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	1.380 Inches Maximum
Nominal Thread Size:	0.164 Inches
Shear Strength:	1760 Double Pounds Per Square Inch
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL22-5-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.