

Description

Fastener Length: 7/8", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL2259
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-450-2288
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL22-5-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.864 Inches Minimum And 0.884 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.0635 Inches Minimum And 0.0645 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.242 Inches Minimum And 0.262 Inches Maximum
Unable To Decode:	Unable To Decode
Grip Length:	0.557 Inches Minimum And 0.567 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Criticality Code Justification:	Aatb And Aaze
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-430 Fed Spec 1st Material Response Overall Or Qq-a-225/9 Fed Spec 2nd Material Response Overall
Material Document And Classification:	Qq-a-430 Fed Spec 1st Material Response Or Qq-a-225/9 Fed Spec 2nd Material Response Overall
Thread Series Designator:	Unjc

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL22-5-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.