

**Description**

Fastener Length: 1-9/64", Thread Size: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                    |
|-------------------------|------------------------------------|
| SKU / Model:            | HL22613                            |
| Minimum Qty (MOQ):      | 25 EA                              |
| NSN:                    | 5320-00-400-4061                   |
| Schedule B:             | 7616.99.5090                       |
| ECCN:                   | EAR99                              |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HL22-6-13 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 1.127 Inches Minimum And 1.147 Inches Maximum  |
| <b>Head Style:</b>                                    | Err-090  |
| <b>Head Height:</b>                                   | 0.055 Inches Minimum And 0.065 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.079 Inches Minimum And 0.081 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.188 Inches Minimum And 0.189 Inches Maximum  |
| <b>Shank Style:</b>                                   | Pin-rivet, Straight, Threaded  |
| <b>Head Major Diameter:</b>                           | 0.295 Inches Minimum And 0.315 Inches Maximum  |
| <b>Head Minor Diameter:</b>                           | 0.205 Inches Minimum And 0.265 Inches Maximum  |
| <b>Unable To Decode:</b>                              | Unable To Decode   |
| <b>Grip Length:</b>                                   | 0.751 Inches Minimum And 0.812 Inches Maximum  |
| <b>Nominal Thread Size:</b>                           | 0.190 Inches   |
| <b>Heat Treatment:</b>                                | As Fabricated Overall  |
| <b>Material:</b>                                      | Aluminum Alloy Overall   |
| <b>Material Document And Classification:</b>          | Qq-a-430,7075,t6 Fed Spec Single Material Response Overall Or Qq-a-225/9 Fed Spec Single Material Response Overall |
| <b>Material Document And Classification:</b>          | Qq-a-430,7075,t6 Fed Spec Single Material Response Or Qq-a-225/9 Fed Spec Single Material Response Overall         |
| <b>Surface Treatment:</b>                             | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this hl pin from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL22-6-13](https://military-fasteners.com/pins/pin_rivets/HL22-6-13) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.