

P/N HL22-6-13

Description

Fastener Length: 1-9/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: HL22613
Minimum Qty (MOQ): 25 EA

NSN: 5320-00-400-4061

Schedule B: 7616.99.5090

ECCN: EAR99

National Motor Freight: 013120, Aluminum Article Noi Sub 6



^{*} See page 2 for technical characteristics

P/N HL22-6-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.127 Inches Minimum And 1.147 Inches Maximum
Head Style:	Err-090
Head Height:	0.055 Inches Minimum And 0.065 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Head Minor Diameter:	0.205 Inches Minimum And 0.265 Inches Maximum
Unable To Decode:	Unable To Decode
Grip Length:	0.751 Inches Minimum And 0.812 Inches Maximum
Nominal Thread Size:	0.190 Inches
Heat Treatment:	As Fabricated Overall
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-430,7075,t6 Fed Spec Single Material Response Overall Or Qq-a-225/9 Fed Spec Single Material Response Overall
Material Document And Classification:	Qq-a-430,7075,t6 Fed Spec Single Material Response Or Qq-a-225/9 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL22-6-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.