

Description

protruding shear head, aluminum alloy, anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | HL2264 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-972-3364 |
| ECCN: | EAR99 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |

NO IMAGE
AVAILABLE

P/N HL22-6-4 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.565 Inches Minimum And 0.585 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.055 Inches Minimum And 0.065 Inches Maximum |
| Width Between Flats: | 0.079 Inches Minimum And 0.081 Inches Maximum |
| Shank Diameter: | 0.189 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Pin-riquet, Straight, Threaded |
| Head Major Diameter: | 0.295 Inches Minimum And 0.315 Inches Maximum |
| Grip Length: | 0.255 Inches Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Heat Treatment: | T-6 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-riquet from our inventory online by visiting https://military-fasteners.com/pins/pin_riquets/HL22-6-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.