

Description

protruding shear head, aluminum alloy, anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------|
| SKU / Model: | HL2266 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-246-0375 |
| ECCN: | EAR99 |
| National Motor Freight: | 013630, Alum Rivets |



* See page 2 for technical characteristics

P/N HL22-6-6 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.690 Inches Minimum And 0.710 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.055 Inches Minimum And 0.065 Inches Maximum |
| Width Between Flats: | 0.079 Inches Minimum And 0.081 Inches Maximum |
| Shank Diameter: | 0.189 Inches Minimum And 0.190 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.295 Inches Minimum And 0.315 Inches Maximum |
| End Item Identification: | W/s: Deep Submergence Systems Programs (dssp); Ah-64-d Longbow; Helicopter, Seahawk H-60; Aircraft, Viking S-3b; Helicopter, Apache Ah-64; Aircraft, Stratolifter C-135; Aircraft, Hercules C-130; Helicopter, Rh-53; Aircraft, Galaxy C-5; Aircraft, Airlifter C-17a |
| Grip Length: | 0.380 Inches Maximum |
| Nominal Thread Size: | 0.190 Inches |
| Heat Treatment: | T-6 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL22-6-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.