

**Description**

protruding shear head, aluminum alloy, anodized

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | HL2266              |
| Minimum Qty (MOQ):      | 10                  |
| NSN:                    | 5320-00-246-0375    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE  
AVAILABLE

## P/N HL22-6-6 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Fastener Length:</b>                               | 0.690 Inches Minimum And 0.710 Inches Maximum   |
| <b>Head Style:</b>                                    | Err-090   |
| <b>Head Height:</b>                                   | 0.055 Inches Minimum And 0.065 Inches Maximum   |
| <b>Width Between Flats:</b>                           | 0.079 Inches Minimum And 0.081 Inches Maximum   |
| <b>Shank Diameter:</b>                                | 0.189 Inches Minimum And 0.190 Inches Maximum   |
| <b>Shank Style:</b>                                   | Pin-rivet, Straight, Threaded   |
| <b>Head Major Diameter:</b>                           | 0.295 Inches Minimum And 0.315 Inches Maximum   |
| <b>End Item Identification:</b>                       | W/s: Deep Submergence Systems Programs (dssp); Ah-64-d Longbow; Helicopter, Seahawk H-60; Aircraft, Viking S-3b; Helicopter, Apache Ah-64; Aircraft, Stratolifter C-135; Aircraft, Hercules C-130; Helicopter, Rh-53; Aircraft, Galaxy C-5; Aircraft, Airlifter C-17a |
| <b>Grip Length:</b>                                   | 0.380 Inches Maximum  |
| <b>Nominal Thread Size:</b>                           | 0.190 Inches  |
| <b>Heat Treatment:</b>                                | T-6 Solution Heat Treated Overall   |
| <b>Material:</b>                                      | Aluminum Alloy 7075 Overall   |
| <b>Material Document And Classification:</b>          | Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall  |
| <b>Surface Treatment:</b>                             | Anodize Overall   |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HL22-6-6](https://military-fasteners.com/rivets/pin_rivets/HL22-6-6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.