

Description

Fastener Length: 41/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL2284
Minimum Qty (MOQ):	1 EA
NSN:	5320-00-338-5824
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HL22-8-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.635 Inches Minimum And 0.655 Inches Maximum
Head Style:	Err-090
Head Height:	0.080 Inches Minimum And 0.090 Inches Maximum
Width Between Flats:	0.095 Inches Minimum And 0.097 Inches Maximum
Shank Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.255 Inches Maximum
Nominal Thread Size:	0.250 Inches
Shear Strength:	4500 Double Pounds Per Square Inch
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL22-8-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.