

Description

Fastener Length: 41/64", Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | HL2284 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5320-00-338-5824 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N HL22-8-4 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.635 Inches Minimum And 0.655 Inches Maximum |
| Head Style: | Err-090 |
| Head Height: | 0.080 Inches Minimum And 0.090 Inches Maximum |
| Width Between Flats: | 0.095 Inches Minimum And 0.097 Inches Maximum |
| Shank Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.387 Inches Minimum And 0.412 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.255 Inches Maximum |
| Nominal Thread Size: | 0.250 Inches |
| Shear Strength: | 4500 Double Pounds Per Square Inch |
| Heat Treatment: | T-6 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL22-8-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.