

Description

protruding tension head oversized for hl20, alloy steel cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL220612
Minimum Qty (MOQ):	10
NSN:	5320-00-502-0750
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N HL220-6-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.065 Inches Minimum And 1.085 Inches Maximum
Head Height:	0.064 Inches Minimum And 0.074 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.2172 Inches Minimum And 0.2182 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.370 Inches Minimum And 0.390 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.755 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Head Style A34 Flat Chamfer
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,c1 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL220-6-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.