

Description

Diameter: 7/32", Grip Length: 11/16", flush tension head, oversized for HL21, alloy steel cadmium plated, HL221 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL221611
Minimum Qty (MOQ):	5
NSN:	5320-01-300-3245
Schedule B:	7318.29.0000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N HL221-6-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.003 Inches Minimum And 1.023 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.791 Inches Minimum And 0.806 Inches Maximum
Shank Diameter:	0.2172 Inches Minimum And 0.2182 Inches Maximum
Shank Style:	Pin-rievet, Straight, Threaded
Head Major Diameter:	0.3765 Inches Minimum And 0.3813 Inches Maximum
Grip Length:	0.683 Inches Minimum And 0.693 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	7100 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty li,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rievet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL221-6-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.