

Description

100°, flush ms24694 tension head, oversized for hl21, alloy steel - cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL22164
Minimum Qty (MOQ):	10
NSN:	5320-01-242-4360
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

## P/N HL221-6-4 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.925 Inches Minimum And 0.945 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.170 Inches Minimum And 0.180 Inches Maximum
<b>Width Between Flats:</b>	0.269 Inches Minimum And 0.289 Inches Maximum
<b>Shank Diameter:</b>	0.4985 Inches Minimum And 0.4995 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.735 Inches Minimum And 0.770 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>End Item Identification:</b>	W/s: Joint Stars Target Radar System; Aircraft, Starlifter C-141
<b>Grip Length:</b>	0.255 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Nominal Thread Size:</b>	0.500 Inches
<b>Heat Treatment:</b>	T-6 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this hi-lok from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL221-6-4](https://military-fasteners.com/pins/pin_rivets/HL221-6-4) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.