

Description

100°, flush ms24694 tension head, oversized for hl21, alloy steel - cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL22164
Minimum Qty (MOQ):	10
NSN:	5320-01-242-4360
National Motor Freight:	013630, Alum Rivets



P/N HL221-6-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.925 Inches Minimum And 0.945 Inches Maximum
Head Style:	Err-090
Head Height:	0.170 Inches Minimum And 0.180 Inches Maximum
Width Between Flats:	0.269 Inches Minimum And 0.289 Inches Maximum
Shank Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.735 Inches Minimum And 0.770 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
End Item Identification:	W/s: Joint Stars Target Radar System; Aircraft, Starlifter C-141
Grip Length:	0.255 Inches Maximum
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.500 Inches
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hi-lok from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HL221-6-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.