

**Description**

Diameter: 5/32", Grip Length: 3/16", flush ms20426 shear head, aluminum alloy, anodized

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | HL2353                                      |
| Minimum Qty (MOQ):      | 20  |
| NSN:                    | 5320-00-438-9509                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



## P/N HL23-5-3 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 0.490 Inches Minimum And 0.510 Inches Maximum  |
| <b>Head Style:</b>                                    | Flush Countersunk  |
| <b>Width Between Flats:</b>                           | 0.0635 Inches Minimum And 0.0645 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.1625 Inches Minimum And 0.1635 Inches Maximum  |
| <b>Shank Style:</b>                                   | Pin-rivet, Straight, Threaded  |
| <b>Head Major Diameter:</b>                           | 0.2874 Inches Minimum And 0.2922 Inches Maximum  |
| <b>Lubrication:</b>                                   | Cetyl Alcohol  |
| <b>Grip Length:</b>                                   | 0.183 Inches Minimum And 0.193 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Nominal Thread Size:</b>                           | 0.164 Inches   |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal  |
| <b>Criticality Code Justification:</b>                | Aazg And Aatb And Aaze   |
| <b>Heat Treatment:</b>                                | T-6 Solution Heat Treated Overall  |
| <b>Material:</b>                                      | Aluminum Alloy 7075 Overall  |
| <b>Material Document And Classification:</b>          | Qq-a-430 Fed Spec 1st Material Response Or Qq-a-225/9 Fed Spec 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625 Mil Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjc   |

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL23-5-3](https://military-fasteners.com/pins/pin_rivets/HL23-5-3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.