

Description

100°, flush ms20426 shear head - aluminum alloy - anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL2356
Minimum Qty (MOQ):	10
NSN:	5320-00-400-5784
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N HL23-5-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.677 Inches Minimum And 0.697 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.063 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.162 Inches Minimum And 0.163 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.287 Inches Minimum And 0.292 Inches Maximum
Grip Length:	0.370 Inches Minimum And 0.380 Inches Maximum
Nominal Thread Size:	0.164 Inches
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	As Fabricated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL23-5-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.