

**Description**

Fastener Length: 3/4", Thread Size: 5/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HL2357
Minimum Qty (MOQ):	10
NSN:	5320-00-959-7328
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics



## P/N HL23-5-7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.740 Inches Minimum And 0.760 Inches Maximum
<b>Head Style:</b>	Flush Countersunk
<b>Width Between Flats:</b>	0.064 Inches Minimum And 0.065 Inches Maximum
<b>Shank Diameter:</b>	0.1625 Inches Minimum And 0.1635 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.287 Inches Minimum And 0.292 Inches Maximum
<b>Grip Length:</b>	0.443 Inches Maximum
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Shear Strength:</b>	1760 Double Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Heat Treatment:</b>	T-6 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HL23-5-7](https://military-fasteners.com/pins/pin_rivets/HL23-5-7) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.