

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|------------------------------------|
| SKU / Model: | HL23611 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-00-508-8425 |
| Schedule B: | 7616.10.5000 |
| ECCN: | 9A991 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HL23-6-11 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 1.003 Inches Minimum And 1.023 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.079 Inches Minimum And 0.081 Inches Maximum |
| Shank Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.349 Inches Minimum And 0.354 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.693 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Shear Strength: | 2540 Double Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Heat Treatment: | T-6 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-430 Mil Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL23-6-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.