

Description

Fastener Length: 1-13/64", Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HL23614
Minimum Qty (MOQ):	15 EA
NSN:	5320-00-091-5154
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi

NO IMAGE
AVAILABLE

P/N HL23-6-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.190 Inches Minimum And 1.210 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.349 Inches Minimum And 0.354 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.880 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Shear Strength:	2540 Double Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Overall Or Qq-a-430,alloy 7075 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HL23-6-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.